DISCOVERY

BUCKSKIN

VillaePaint
甄图艺墅家

Explore the natural world. Discovery



8456 A



8456 B

8456 C

BUCKSKIN

8459 M

8428 M

8432 M

8425 M

8457 M

8429 M



8481 D

8481 B

8481 A

8467 D

8467 B

8467 A

8470 D

8470 B

8470 A

8456 D

8456 B

8456 A





8496 D
8479 D
8496 C
8479 C
8496 B
8479 B
8496 A
8479 A



8451 A
8451 B
8451 D
8448 A
8448 B
8448 D
8425 A
8425 B
8425 D
8468 A
8468 B
8468 D



8498 D

8484 D

8498 C

8484 C

8498 B

8484 B

8498 A

8484 A



8497 A

8497 B

8497 D

8482 A

8482 B

8482 D

8541 A

8541 B

8541 D

8455 A

8455 B

8455 D

8471 D

8471 C

8471 B

8471 A



8437 A

8437 B

8437 D

8438 A

8438 B

8438 D

8542 A

8542 B

8542 D

8457 A

8457 B

8457 D





8474 D

8474 C

8474 B

8474 A



8534 A

8534 B

8534 D

8463 A

8463 B

8463 D

8476 A

8476 B

8476 D

8539 A

8539 B

8539 D

8538 D

8537 D

8538 C

8537 C

8538 B

8537 B

8538 A

8537 A



8428 A

8428 B

8428 D

8446 A

8446 B

8446 D

8442 A

8442 B

8442 D

8536 A

8536 B

8536 D





Discovery--BUCKSKIN series is a series that imitates natural buckskin effects. It uses unique polymer polymerization technology and combines natural mineral pigments to simulate the real texture and color of buckskin in nature. This series of coatings not only has excellent adhesion and durability, but also has good breathability and environmental protection performance, and can maintain bright colors and clear textures for a long time.

Product characteristics:

1. Realistic texture: Through special technology, the delicate texture of buckskin can be accurately simulated, showing a natural and realistic effect.
2. Environmental protection and health: It uses environmentally friendly raw materials and does not contain toxic and harmful substances. The products comply with relevant national environmental protection standards.
3. Excellent adhesion: Strong adhesion to the base layer, not easy to peel, crack or deform.
4. Excellent expression: rich colors and delicate texture, creating a unique artistic atmosphere.
5. Moisture-proof: good breathability, moisture-proof, moisture-absorbing, and not afraid of "going back to the south".

Scope of application:

This series of coatings is suitable for indoor walls, ceilings and other decorative surfaces, and is especially suitable for interior decoration in homes, villas, hotels, clubs and other places that pursue natural and original styles.

Construction process description:

1. Base layer treatment: Make sure the wall surface is dry, clean, free of oil stains, and free of floating dust. If there are cracks or uneven areas, they need to be repaired and smoothed in advance. Construction of new walls must be carried out after they are fully dry.
2. Penetrating primer treatment: Use the matching penetrating primer PM-NB104 to penetrate and cure the putty base layer through roller coating, spraying or brushing. (Note: The packaging specification of penetrating primer PM-NB104 is 5KG/barrel, and the theoretical coating rate per kilogram is about 10-15 square meters).
3. Primer treatment: Use the matching primer PM-B701 and apply it evenly on the wall through roller coating, spraying or brushing to enhance the adhesion between the surface coating and the base layer and improve the durability of the overall coating. (Note: The packaging specification of primer PM-B701 is 5KG/barrel, and the theoretical coating rate per kilogram is about 6-8 square meters).
4. Buckskin series brushing: Use special brushes or professional tools according to the specific effect to perform the first brushing process of the buckskin series on the wall. When brushing, apply the corresponding texture effect according to the specific process. After the first coat of buckskin series is completely dry, continue with the second coat of buckskin series. (Note: The packaging specification of buckskin series is 5KG/barrel, and the theoretical coating rate per kilogram is about 4-6 square meters).
5. Acceptance and cleaning: After the construction is completed, conduct a comprehensive inspection to ensure that there are no defects or omissions, and the construction site should be cleaned up in a timely manner to keep the environment clean and tidy.

Please strictly follow the above process for construction to ensure the best decorative effect and service life. At the same time, the specific construction process may be slightly adjusted due to actual conditions, so please operate flexibly according to site conditions.

Precautions:

1. Avoid mixing with other coatings during construction to avoid affecting the effect.
2. The technique should be kept uniform during construction to avoid color difference, brush marks, etc.
3. After the construction is completed, ensure that the coating is fully dry and avoid contact and friction to avoid affecting the quality of the coating.
4. After each use, be sure to close the paint can tightly and store it in an environment with a temperature between +10°C and +30°C.
5. Pay attention to protection during construction, avoid direct contact with skin, and protect eyes and face. In case of accidental contact, wash immediately with clean water. If you feel unwell, seek medical advice promptly.
6. The color block of the product is produced as a sample for color reference. The final color is subject to actual usage.



觅境--鹿皮系列中是仿自然界鹿皮效果系列，采用独特的高分子聚合技术，结合天然矿物质颜料，旨在模拟自然界中鹿皮的真实纹理和色泽。该系列涂料不仅具有优异的附着力和耐久性，同时具备良好的透气性和环保性能，能够长时间保持色彩的鲜艳和纹理的清晰。

一、产品特性

1、真实纹理：通过特殊工艺，能够精确模拟鹿皮的细腻纹理，呈现出自然、逼真的效果。
2、环保健康：采用环保原料，不含有毒有害物质，产品符合国家相关环保标准。
3、优异附着力：与基层粘结力强，不易剥落、不开裂、不变形。
4、卓越表现力：色彩丰富，质感细腻，营造独特艺术氛围。
5、防潮：透气性好、防潮、吸潮，不惧"回南天"。

二、适用范围

该系列涂料适用于室内墙面、天花板等装饰面，特别适用于追求自然、原始风格的家居、别墅、酒店、会所等场所的室内装饰。

三、施工流程说明

1、基层处理：确保墙面干燥、清洁、无油污、无浮灰，如有裂缝或凹凸不平的地方需提前修补平整。对新建墙体需待其充分干燥后进行施工。
2、渗透底漆处理：使用配套的渗透底漆PM-NB104，通过滚涂、喷涂或者刷涂的工艺，对腻子基层进行渗透和固化处理。
（注：渗透底漆PM-NB104包装规格5KG/桶，每公斤理论涂布率约10-15平方）。
3、底漆处理：使用配套的底漆PM-B701，通过滚涂、喷涂或者刷涂的工艺，均匀涂刷于墙面，增强面层涂料与基层的附着力，提高整体涂层的耐久性。
（注：底漆PM-B701包装规格5KG/桶，每公斤理论涂布率约6-8平方）。
4、鹿皮系列刷涂：根据具体效果使用专用刷子或专业工具，在墙面上进行鹿皮系列的第一遍刷涂工艺，刷涂时根据具体的工艺刷涂对应的纹理效果。第一遍鹿皮系列完全干燥以后，继续进行第二遍鹿皮系列的施工。
（注：鹿皮系列包装规格5KG/桶，每公斤理论涂布率约4-6平方）。
5、验收与清理：施工完毕后进行全面检查，确保无瑕疵、无遗漏，并及时清理施工现场，保持环境整洁。

请严格按照上述流程进行施工，确保最佳的装饰效果和使用寿命。同时，具体施工工艺可能因实际情况略有调整，请根据现场条件灵活操作。

四、注意事项

1、施工过程中应避免与其他涂料混合使用，以免影响效果。
2、施工时应保持手法均匀，避免出现色差、刷痕等现象。
3、施工完成后，应确保涂层充分干燥，避免触碰、摩擦，以免影响涂层质量。
4、每次开盖使用后，务必盖紧涂料罐，并且存放在温度介于 +10°C — +30°C 之间的环境中。
5、施工过程中要注意防护，避免直接接触皮肤，保护好眼睛和脸部。如不慎接触，应立即用清水清洗，如有不适应及时就医。
6、产品色块为样品制作，供颜色参考，最终颜色以实际使用情况为准。

VillaePaint
甄图艺墅家

GROWTH CULTURE 格式文化
广东格式装饰文化发展股份有限公司
GROWTH DECORATION CO.,LTD

地址：广东省佛山市顺德区容桂容里社区昌宝西路50号
Add：NO.50,Western Changbao road,Rongli residents'committee,
Ronggui,Shunde,Foshan,Guangdong
Tel：0086 757 28308787　　Fax：0086 757 23617576
Email：info@growthgroup.com.cn